

# Moore 382 Logic and Sequence Controller Model Selection

	Model No. 3 8 2						
<b>Type</b>							
Basic	B						
Expanded	E						
<b>Power Requirement</b>							
120 Vac (+10%, -15%) 47 to 63 Hz (see note 1)	A						
24 Vac (+10%, -15%) 47 to 63 Hz	B						
24 Vdc (+20%, -15%)	C						
220/240 Vac (+10%, -15%) 47 to 63 Hz (see note 1)	E						
*Note 1: On newer models the "E" is no longer available. It is merged with "A"; 120/240 VAC (85 to 264 VAC) 47 to 63 Hz. Please specify your power input requirement.							
<b>Mounting Case</b>							
Screw Terminals, 20		1					
Screw Terminals, 40 (Required on 382E)		2					
Not Required		N					
<b>Operators Panel</b>							
Analog and Digital Displays			1				
Not Required			N				
<b>Third Input Options</b>							
Voltage (Additional 1 to 5 Vdc)				V			
Thermocouple (J, K, T, E, S, R, B) and Millivolt				T			
RTD (DIN curve; US curve)				D			
Frequency				F			
Computer (Dual Pulse and Pulse Direction)				C			
Not Required				N			
<b>Link Interface</b>							
Local Instrument Link (RS422, Half-Duplex)						1	
Not Required						N	
<b>Electrical Classification</b>							
CSA							C
FM							F
Not Available							N
	Model No. 3 8 2						
	Example: 3 8 2	B	A	1	1	V	1 F

Please let us know the exact model you require. We can often customize units for your specific needs.



Classic Automation LLC  
 795 Monroe Avenue  
 Rochester, NY 14607  
 USA

[www.classicautomation.com](http://www.classicautomation.com)

+1 (585) 241-6010

[customerservice@classicautomation.com](mailto:customerservice@classicautomation.com)